

# Incandescent Work Lights

BL-15



# 12 volt

**PROLITE™**
**PROLITE™ SPECIALTY INCANDESCENT LIGHTING**

Part #	Description	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating
BL-15	12V automotive work light with battery clamps. Special bulb included. On-off switch in handle. Swivel hook.	60W, 12V included	15 ft.	18/2 SPT1	12V DC


**TL-25P  
TL-25PN  
TL-6P**

**TL-50GM  
TL-25GM‡**

**MCL6P**
**PROLITE™**
**PROLITE™ INCANDESCENT WORK LIGHTS**

Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating
TL-6P	On-off switch built into handle plastic swing-open bulb guard with swivel hook.	n/a	75W	6 ft.	18/2 SJT	75W 125V
TL-25P	On-off switch, plastic swing open guard swivel hook.	n/a	75W	25 ft.	18/2 SJT	75W 125V
TL-25PN	Same as TL-25P except no switch meets NEC 511 (1) for use in commercial garages. Cord and lamp head must be supported so that they cannot reach within 18" of the floor.	n/a	75W	25 ft.	18/2 SJT	75W 125V
TL-25GM‡	On-off switch built into handle. Grounded metal swing-open bulb guard with hanging hook.	Built-in	100W	25 ft.	16/3 SJT	1625W 13A 125V
TL-50GM	On-off switch, grounded swing open metal guard, fixed hook.	Built-in	100W	50 ft.	16/3 SJT	1625W 13A 125V
MCL6P	4 in 1 incandescent work light, stick it, clamp it, hang it and stand it. With aluminum reflector shade.	No	60W	6 ft.	18/2 SJWT	60W .480A 125V

Bulb not included - maximum bulb rating shown ‡Display tray pack packaging


**TL-25GM-CB**

**TLP-25GM-CB  
TLP-50GM-CB**
**PROLITE™  
PROFESSIONAL**
**PROLITE™ PROFESSIONAL INCANDESCENT WORK LIGHTS**

Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating
TL-25GM-CB	On-off switch, grounded swing open metal guard, fixed hook.	Built-in w/circuit breaker	100W	25 ft.	16/3 SJT	1625W 13A 125V
TLP-25GM-CB	On-off switch, grounded metal guard 360° rotary hook, all weather cord.	Built-in w/circuit breaker	100W	25 ft.	16/3 SJWTOW	1625W 13A 125V
TLP-50GM-CB	On-off switch, grounded metal guard 360° rotary hook, all weather cord.	Built-in w/circuit breaker	100W	50 ft.	16/3 SJWTOW	1625W 13A 125V

\*Bulb not included - maximum bulb rating shown


**HTL-25M-CB  
HTL-50M-CB**
**PROLITE™  
INDUSTRIAL**
**PROLITE™ INDUSTRIAL INCANDESCENT WORK LIGHTS**

Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating
HTL-25M-CB	Grounded metal reflector with heavy duty metal reflector/bulb guard, on-off switch.	Built-in w/circuit breaker	100W	25 ft.	14/3 SJWT	1875W 15A 125V
HTL-50M-CB	Grounded metal reflector with heavy duty metal reflector/bulb guard, on-off switch.	Built-in w/circuit breaker	100W	50 ft.	14/3 SJWT	1875W 15A 125V

\*Bulb not included - maximum bulb rating shown



TLS-50  
TLS-100



TLS-100J2  
TLS-50J3  
TLS-100J3



PRO <sub>Δ</sub> LITE™ INDUSTRIAL INCANDESCENT WORK LIGHT						
Part #	Description	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating	
TLS-50	Molded-on weather resistant lamp sockets with durable plastic bulb guards spaced on 10 ft. centres. Linkable.	5x 150W	50 ft.	12/3 STW	2500W 15A 125V	
TLS-100	Molded-on weather resistant lamp sockets with durable plastic bulb guards spaced on 10 ft. centres. Linkable.	10x 150W	100 ft.	12/3 STW	2500W 15A 125V	
TLS-100J2**	Molded-on weather resistant lamp sockets with plastic bulb guards spaced on 10 ft. centres. Non-linkable.	10x 150W	100 ft.	14/2 SJTW	1875W 15A 125V	
TLS-50J3**	Molded-on weather resistant lamp sockets with metal cage bulb guards spaced on 10 ft. centres. Linkable.	5x 150W	50 ft.	12/3 SJTW	2500W 15A 125V	
TLS-100J3**	Molded-on weather resistant lamp sockets with metal cage bulb guards spaced on 10 ft. centres. Linkable.	10x 150W	100 ft.	12/3 SJTW	2500W 15A 125V	

\*Bulb not included - maximum bulb rating shown

\*\*UL specified only, not CUL



5000A-30G



5000-30G-CB



PRO <sub>Δ</sub> REEL™ INCANDESCENT RETRACTABLE CORD REEL WORK LIGHTS						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating
5000A-30G	Powder coated metal reel housing, grounded metal guard, on-off switch.	Built-in	75W	30 ft.	16/3 SJT	1250W 10A 125V
5000-50G-CB	Powder coated metal reel housing, grounded metal guard, on-off switch.	Built-in w/circuit breaker	75W	50 ft.	18/3 SVT	875W 7A 125V

\*Bulb not included - maximum bulb rating shown

5000-35G-SSP\*



5000A-30G-CB  
5000A-30G-CBP



8050M-W



PRO <sub>Δ</sub> REEL™ INCANDESCENT RETRACTABLE CORD REEL WORK LIGHTS						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge Cord Type	Max. Rating
5000A-30G-CB	Powder coated metal reel housing, grounded metal guard, on-off switch.	Built-in w/circuit breaker	75W	30 ft.	16/3 SJT	1250W 10A 125V
5000A-30G-CBP	Same as 5000A-30G-CB with powder coated metal reel, metal bulb guard with swivel hook and 30 ft. all-weather cord.	Built-in w/circuit breaker	75W	30 ft.	16/3 SJTOW	1250W 10A 125V
5000-35G-SSP	Powder coated steel reel with auto switching feature, nylon guard.±	n/a	75W	35 ft.	18/3 SJT	75W 125V
8050M-W	Industrial grade reel housing. Quick release mounting bracket. Convenient carrying handle. 360° reflector guard with rotary hook.	Built-in w/circuit breaker	100W	50 ft.	14/3 SJTW	1625W 13A 125V

\*Bulb not included - maximum bulb rating shown

± For safety code compliance the reel must be mounted a minimum of 12' above the floor and the cord and lamp head must be supported so they cannot reach 8" above the floor